



# 180° MICRO-COMPUTER AUTO SHRIMP/FISH FEEDER

## 全佳牌180°微電腦自動魚蝦用投料機

- 投料量可調(1-16檔)
- 投料時長可調(1-60秒)
- 投料間隔可調(1-60分鐘)
- 飼料粉碎率<5%
- 24小時內可設最多8組投料時段
- 投料面積(半徑)可調



1. LCD display micro-computer controller is able to set up the feeding time, interval, quantity and distance for your farming requirement (Maximum 8 sets of feeding time and mode can be set in 24 hrs).
2. The small & speed regulated main motor can easily drive the 4-blade fan to spray the feed through centrifugal force.
3. The vibration motor can drop the feed accurately.
4. The special design of the controller which is installed inside the drum makes it waterproof.
5. The fish feeder working platform is 2M away from the pond shore and 1M height from water surface.

MODEL	MAIN MOTOR	VIBRATION MOTOR	VOLT	PHASE	CAPACITY	FEEDING DISTANCE
UAF-F80120.3S/ UAF-180D	150W, 2800RPM	30W	220V	SINGLE PHASE	100L/ 240L	2-17M

FAN SURFACE	COVERAGE AREA	MAX FEEDING RATE	MEASUREMENT & NET WEIGHT	FEED SMASHING RATE
140°	30-360m <sup>2</sup>	8 Kg/MIN	56 × 56 × 106cm 22 Kg	<5%